

Bosch 32C Specifications	
Part Number	BC3200RA
Installation	External/ Internal*
Ignition	Electronic
L/min (25°C rise)	32
Min. inlet water pressure (kPa)	98
Max. inlet water pressure (kPa)	980
Mj/H	217 MJ/hr
Star Rating	6
Temperature Range	The appliance BC3200RA is preset to 55°C and can be adjusted by connecting the connector of the harness to 50°C, 75°C and 85°C. And it can be adjusted by programming the CPU on the PCB to 40°C, 60°C and 65°C. BC3200RA5 is preset to 50°C and can be adjusted by connecting the connector or programming the CPU on the PCB to 40°C and 42°C. These appliances offer two types of remote controllers as optional accessories. When a remote controller is connected, BC3200RA allows settings from 37°C - 48°C in 1°C steps plus seven additional settings of 50°C, 55°C, 60°C, 65°C, 70°C, 75°C and 80°C. BC3200RA5 allows settings from 37°C - 48°C in 1°C and 50°C.
Min. Flow (L/min)	2.5L/min
Min. constant water pressure for Max. flow (kPa)	200 kPa
Antifrost	Standard
Gas Type	NG/LPG
Electrical Supply	230 - 240 VAC 50 Hz (10amp weatherproof power point required within 500mm of the unit)
Temperature Controller	Compatible with the RCM3211 and the RCS3211
Unit Height x Width x Depth (mm)	615 x 464 x 240
Carton Weight (Kg)	39
Flue Pipe Sizes (mm)	100mm
Warranty	
<i>Commercial</i>	
Parts and Labour	2 Years
Heat Exchanger (part only)	5 Years
<i>Domestic</i>	
Parts and Labour	3 Years
Heat Exchanger (part only)	10 Years
Pipe Connection Size	
Natural gas (NG)	20mm
LP gas	20mm
Cold Water	20mm
Hot Water	20mm
Condensate Drain	15mm

*Flueing required - must be a type that is Bosch approved